KF Valves
KF Series FA/FAE Two-Piece Trunnion Mounted Ball Valves



CIRCOR ENERGY

Continuously Improving
Flow Control

KF Series FA/FAE Two-Piece Trunnion Mounted Ball Valves

Features

- Double block and bleed
- Self relieving seat
- Anti-blowout stem design
- O-rings plus firesafe packing prevents leakage
- Corrosion resistant low friction bearings
- Inconel® wave springs to provide upstream and downstream sealing
- Stainless steel sealant injection fittings for emergency stem or seat sealing
- Minimized torque required to open and close valve
- Antistatic device for grounding of the ball, stem/trunnion and body
- Integral topworks direct mounting pad
- 8" & larger valves are equipped with lifting lugs


This high quality two-piece split body trunnion mounted ball valve conforms to API 6D, ASME B 16.34 and ASTM specifications. Devlon® seats are standard.

All seats are retained in metal holders which are spring-loaded against the ball for low pressure, firesafe sealing. Series FA/FAE valves are offered in: 2" thru 12" class 150 & 300



Firesafe Function

In case of fire and seat construction damage, firesafe requirements are accomplished with automatic metal-to-metal positive sealing.




Before *After*

Contents

Valve Assembly Part Number Codes . . . 3
Buttweld End Valve Assembly Part Number Codes . . . 4
Design Features . . . 5
Technical Seating Features, Availability & Maximum Pressure Ratings . . . 6
Applicable Standards . . . 7
Component Parts, 2"- 6" . . . 8
Component Parts, 6"-12" . . . 9
Dimensional Data, API 6D & ASME B 16.34, Class 150 . . . 10
Dimensional Data, API 6D & ASME B 16.34, Class 300 . . . 11
Topworks & Stem Data . . . 12
Engineering Data . . . 13
Optional Accessories & Installation . . . 14

KF Series FA/FAE Part Number Codes



Ø • Domestic
E • Global

Base Number
See Chart Below

Body/Bolting Material
1 • CS / CS
2 • SS / CS (Xylan®)
8 • LTCS / LTCS

Trim & Drain
2 • 316SS
3 • 410SS or CA15M
6 • CS (3 mil ENP)
7 • LTCS (3 mil ENP LTCS Ball, SS Stem, CS Seats & SS Fittings)
8 • LTCS (1 mil ENP LTCS Ball, SS Stem, CS Seats & SS Fittings)
B • 316SS w/Drain
C • 410SS w/Drain
D • CS (3 mil) w/Drain
E • LTCS (3 mil) w/Drain
F • LTCS w/Drain

Seat Insert
2 • Teflon®
5 • HT4 (PEEK™)
9 • Devlon®

O-Ring
2 • Viton® A (75 Duro)
4 • EPDM
5 • Aflas®
8 • LT Buna N
A • James Walker® Viton®
F • Elast-O-Lion® 985
G • HNBR
N • Low Temp (HNBR) KA-183 -50˚F

Specifications
4 • NACE Cl. III B7/2H Bolting / Firesafe
6 • NACE Cl. II B7M/2HM Bolting / Firesafe

Bolting Finish/Body & Adaptor
1 • Black
2 • Zinc Plated
3 • Xylan® Coated (CS/LTCS Only)
4 • Cadmium Plated

Actuation
1 • Handle (2"- 8" Only)
3 • Gear Operator
4 • Handle w/Locking Device (2"- 8" Only)
6 • Gear Operator w/Locking Device
9 • Bare Stem
A • For Actuator

Process Codes
(Last two digits used ONLY when Process Codes are required.)

Ø 3759 - 1 6 9 G 4 1 1 XX

Example


(i.e. ØXXXX - XXXXXXXXX) - Domestic
(i.e. EXXXX - XXXXXXXXX) - Global

Asterisk (*) in lieu of dash (-) in Assembly Part Number indicates customer requires source inspection. (i.e. XXXXX * XXXXXXXXX)

Assembly Base Numbers, RF

Class	Size (in.)												
	2FP	3RP	3FP	4RP	4FP	6RP	6FP	8RP	8FP	10RP	10FP	12RP	12FP
150	3758	3759	3760	3761	3762	3763	3764	3765	3766	3767	3768	3769	3770
300	3778	3779	3780	3781	3782	3783	3784	3785	3786	3787	3788	3789	3790

KF Series FA/FAE Buttweld End Assembly Part Number Codes



Ø • Domestic **E** • Global

Base Number
See Chart Below

End Connection
3 • WE **4** • RF x WE

Weld End Wall Thickness
See Weld Chart Below

NACE Conformance Body / Bolting Material (Finish)

NACE III / Cl. III Bolting	NACE II / Cl. II Bolting
A • CS / B7 (Black) (KF Std.)	**N** • CS / B7M (Black)
F • CS / B7 (Cadmium)	**R** • CS / B7M (Cadmium)
G • CS / B7 (Zinc)	**U** • CS / B7M (Zinc)

Trim & Drain

2 • 316SS	**B** • SS w/Drain
6 • CS (3 mil ENP) (KF Std.)	**D** • CS (3 mil ENP) w/Drain

Seat Insert / FS

B • Teflon® / FS	**E** • Devlon® / FS (KF Std.)
C • HT4 (PEEK™) / FS	

Seal Material

2 • Viton® A (75 Duro)	**F** • Elast-O-Lion® 985
4 • EPDM	**G** • HNBR (KF Std.)
5 • Aflas®	**N** • Low Temp (HNBR) KA-183 -50°F
A • James Walker® Viton®	

Actuation

1 • Handle (2"- 8" Only)	**6** • Gear Operator w/Locking Device
3 • Gear Operator	**9** • Bare Stem
4 • Handle w/Locking Device (2"- 8" Only)	**A** • For Actuator

Process Codes
(Last two digits used ONLY when Process Codes are required.)

Ø 8304 - 3 17 A 6 E G 1 XX

Example

Asterisk (*) in lieu of dash (-) in Assembly Part Number indicates customer requires source inspection.
(i.e. XXXXX * XXXXXXXXX)

(i.e. ØXXXX - XXXXXXXXX) - Domestic
(i.e. EXXXX - XXXXXXXXX) - Global

Assembly Base Numbers


Class	Size (in.)						
	2FP	3FP	4FP	6FP	8FP	10FP	12FP
150	8300	8302	8304	8306	8308	8310	8312
300	8314	8316	8318	8320	8322	8324	8326

KF Series FA/FAE Buttweld Schedule Codes for Assembly Part Number


Pipe Description	Nominal Pipe Size (in.) / KF Schedule Code													
	2	Code	3	Code	4	Code	6	Code	8	Code	10	Code	12	Code
Outside Dia. (in.)	2.375		3.500		4.500		6.625		8.625		10.750		12.750	
(STD) Standard	—	—	—	—	.237	17	.280	22	.322	28	.365	32	.375	33
Schedule 40	.154	08	.216	14	.237	17	.280	22	.322	28	.365	32	.406	35
Schedule 60	—	—	—	—	—	—	—	—	.406	35	.500	39	.562	42
XS	.218	15	.300	24	.337	30	.432	36	.500	39	.500	39	.500	39
Schedule 80	.218	15	.300	24	.337	30	.432	36	.500	39	.593	43	.687	48
Schedule 120	—	—	—	—	.438	38	.562	42	.718	49	.843	52	1.000	58
Schedule 160	.343	31	.438	38	.531	40	.718	49	.906	55	1.125	62	1.312	68
XXS	.436	37	.600	44	.674	47	.864	53	.875	54	1.000	58	1.000	58

Consult factory for other wall thicknesses.


KF Series FA/FAE Design Features




1




2




3




4




5



6



7 *Garloc DU stem and lower trunnion, 2"-4" bore*



Teflon® and glass liner w/316SS housing integral trunnion w/trunnion blocks, 6"-12" bore

1 Firesafe Standard Double Seal

2"FP - 12" Bore, class 150 & 300

- **a** Weather seal
- **b** Stem seal
  braided carbon rope
- **c** Primary stem seal

2 Antistatic Device*

A stainless steel grounding plunger between the body/stem and stem/ball permits electrical continuity.

*2"-4" bore antistatic accomplished through trunnion bearing.

3 Lubricant/Emergency Seat Seal

Special sealants may be injected into fittings that are located on the adapter flanges to restore sealing integrity if seat sealing surface is damaged.

4 Emergency Sealant Injection System

The sealant injection system located on the body can be utilized in case of emergencies, o-ring damage, or if stem leakage occurs.

5 Double Sealed Envelope Connections 2"- 4" Bore

A combination of an o-ring and firesafe gasket ensures a positive seal.

6 Body/Adapter Seal Connection 6"-12" Bore

An o-ring on this connection insures a positive seal.

7 Heavy Duty Bearings

Heavy duty bearings balance the pressure load on the ball by reducing friction between ball and seat resulting in smooth and easy operation of valve.

KF Series FA/FAE Technical Seating Features

Double Block and Bleed

The double block and bleed condition is available in all seat design configurations. When the ball is in the closed position the body cavity pressure may be drained down to 'zero' by opening the bleed valve and draining the fluid by removing the drain plug. Each seat works independently assuring tight shut off seal against ball on the upstream and downstream side.


Self Relieving Seat Design

Upstream Seat


The difference in the area (D1) times the line pressure forces the seat against the ball surface. Also the springs behind the seat adds the force to the seat which keeps the seat in contact with the ball surface by providing the tight seal.

Downstream Seat

When the body cavity pressure exceeds the spring pressure, automatic pressure relief will occur by relieving the body cavity pressure past the downstream seat. This eliminates the need for the body relief valve.



Double Block and Bleed



Self Relieving Seat Design

Availability & Maximum Pressure Ratings, ASME B 16.34 & API 6D

Class	Standard	Size (in.)												
		2FP	3RP	3FP	4RP	4FP	6RP	6FP	8RP	8FP	10RP	10FP	12RP	12FP
150	ASME B 16.34	285	285	285	285	285	285	285	285	285	285	285	285	285
150	API 6D	275	275	275	275	275	275	275	275	275	275	275	275	275
300	ASME B 16.34	740	740	740	740	740	740	740	740	740	740	740	740	740
300	API 6D	720	720	720	720	720	720	720	720	720	720	720	720	720

KF Series FA/FAE Applicable Standards

The following list contains the most important applicable standards for ball valves. KF valves may be designed, manufactured and tested in accordance with other international standards on request.

API - American Petroleum Institute

Spec. 6D
Specification for pipeline valves.

Std. 607
Fire test for soft seated quarter-turn valves.

Spec. 6FA
Specification for fire testing of valves.

Std. 598
Valve inspection and test.

Std. 605
Large diameter carbon steel flanges.

ASME/ANSI - American National Standard Institute

B 16.5
Steel pipe flanges and flanged fittings.

B 16.10
Face-to-face and end-to-end dimensions of ferrous valves.

B 16.25
Butt welding ends.

B 16.34
Steel valves - flanged and butt welding ends (pressure & temperature ratings).

B 31.3
Chemical plant and petroleum refinery piping.

B 31.4
Liquid petroleum transportation piping systems.

B 31.8
Gas transmission and distribution piping systems.

British Standards

BS 1503
Specification for steel forgings for pressure purposes.

BS 1504
Specification for steel castings for pressure purposes.

BS 2080
Face-to-face, center-to-face, end-to-end, and center-to-end dimensions of flanged and butt welding end steel valves for the petroleum, petrochemical and allied industries.

EC - European Community

CE Marked
(P.E.D. 97/23/EC, Cat. 3)

ISO - International Organization for Standardization

ISO 9001:2000
Quality systems - Model for quality assurance in design/development, production, installation and servicing.

ISO 15156
For use in H_2S containing environments in oil and gas production.

MSS - Manufacturers Standardization Society

SP 6
Standard finishes for contact faces of pipe flanges and connecting - end flanges of valves and fittings.

SP 25
Standard marking system for valves, fittings, flanges and unions.

SP 55
Quality standard for steel castings - visual method.

Hydrogen Sulfide (H_2S Environments)

NACE MR0175

ISO 15156
General principles for cracking resistant materials in H_2S containing environments in oil & gas production.


CSA - Canadian Standards Association

CSA Z245.15-09
Standard for steel valves for intended use in oil or gas pipeline systems.

CSA Z662-07
Oil and gas pipeline systems.




KF Series FA/FAE Component Parts, 2"FP-6"RP



Parts List

Part No.	Description
1	Body
2	Adapter
3	Stem Assembly
4	Ball
5	Stem Seal
6	Trunnion Support
7	Seat
8	Seat O-Ring
9	Seat Sub Seal
10	Stem Bearing
11	Thrust Bearing
13	Trunnion Bearing
14	Body Seal
15	Wave Spring
16	Stop Screw
17	Stop Plate
18	Retainer
20	Injection Fitting
21	Bleed Valve
25	Hex Nut
26	Stud


KF Series FA/FAE Component Parts, 6"FP-12"FP





Parts List

Part No.	Description
1	Body
2	Adapter
3	Stem Assembly
4	Ball
5	Stem Seal
7	Seat
8	Seat O-Ring
9	Seat Sub Seal
10	Stem Bearing
11	Thrust Bearing
12	Trunnion Support
13	Trunnion Bearing
14	Body Seal
15	Wave Spring
16	Stop Screw
17	Stop Plate
18	Retainer
20	Injection Fitting
21	Bleed Valve
24	Key, 10"FP thru 12"FP Only
25	Hex Nut
26	Stud

KF Series FA/FAE Dimensional Data








Dimensional Data (in., mm), 2"FP-12"FP, Class 150, API 6D & ASME B16.34

Size (in.)	Weight (lbs.)		Dimension (in.)													
	Valve Only	w/Gear Op.	A	B	C	D	E	F Top of Handle	F CL of H/Whl.	G	H	U	Y	Z	AA	BB
2 x 2	31	43	2	7.00	3.13	6.00	4.94	6.88	5.00	8.50	1.06	3.88	8	2.75	3.56	7.19
3 x 2	33	46	2	8.00	4.00	7.50	4.94	6.88	5.00	8.50	1.06	3.88	8	2.75	3.56	7.19
3 x 3	52	65	3	8.00	3.88	7.50	6.63	8.25	6.50	15.00	1.25	5.38	8	2.75	4.50	7.19
4 x 3	60	73	3	9.00	4.50	9.00	6.63	8.25	6.50	15.00	1.25	5.38	8	2.75	4.50	7.19
4 x 4	78	91	4	9.00	4.50	9.00	7.44	9.00	7.31	15.00	1.25	6.19	8	2.75	5.25	7.19
6 x 4	110	123	4	15.50	5.25	11.00	7.44	9.00	7.31	15.00	1.25	6.19	8	2.75	5.25	7.19
6 x 6	204	234	6	15.50	7.75	11.00	9.50	10.81	9.25	48.00	2.09	7.00	12	2.50	—	9.25
8 x 6	271	301	6	18.00	9.00	13.50	9.50	10.81	9.25	48.00	2.09	7.00	12	2.50	—	9.25
8 x 8	365	429	8	18.00	9.00	13.50	11.56	12.59	10.38	48.31	2.38	8.75	18	3.50	—	11.94
10 x 8	456	520	8	21.00	10.50	16.00	11.56	12.59	10.38	48.31	2.38	8.75	18	3.50	—	11.94
10 x 10	528	605	10	21.00	10.50	16.00	14.31	—	13.38	—	3.19	11.25	24	4.63	—	14.63
12 x 10	648	725	10	24.00	12.00	19.00	14.31	—	13.38	—	3.19	11.25	24	4.63	—	14.63
12 x 12	794	899	12	24.00	12.00	19.00	15.69	—	14.75	—	3.19	12.63	24	4.63	—	14.63

Size (in.)	Weight (kg)		Dimension (mm)													
	Valve Only	w/Gear Op.	A	B	C	D	E	F Top of Handle	F CL of H/Whl.	G	H	U	Y	Z	AA	BB
2 x 2	14.1	19.5	50.8	178	79.4	152	125.4	174.6	127	216.9	27.0	98.4	203.2	69.9	90.5	182.6
3 x 2	15.0	20.9	50.8	203	102	191	125.4	174.6	127	216.9	27.0	98.4	203.2	69.9	90.5	182.6
3 x 3	23.6	29.5	76.2	203	98.4	191	168.3	209.6	165	381	31.8	136.3	203.2	69.9	114.3	182.6
4 x 3	27.2	33.1	76.2	229	114.3	229	168.3	209.6	165	381	31.8	136.3	203.2	69.9	114.3	182.6
4 x 4	35.4	41.3	101.6	229	114.3	229	188.9	228.6	185.7	381	31.8	157.2	203.2	69.9	114.3	182.6
6 x 4	49.9	55.8	101.6	394	133.3	279	188.9	228.6	185.7	381	31.8	157.2	203.2	69.9	133.4	182.6
6 x 6	92.5	106.1	152	394	196.8	279	241	274.6	235.0	1219	53.2	177.8	304.8	63.5	133.4	235.0
8 x 6	122.9	136.5	152	457	229	342.9	241	274.6	235.0	1219	53.2	177.8	304.8	63.5	—	235.0
8 x 8	165.6	194.6	203	457	229	342.9	293.7	319.9	263.5	1227	60.3	222.3	457.2	88.9	—	303.2
10 x 8	206.8	235.9	203	533	267	406	293.7	319.9	263.5	1227	60.3	222.3	457.2	88.9	—	303.2
10 x 10	239.5	274.4	254	533	267	406	363.6	—	339.7	—	81.0	285.8	609.6	117.5	—	371.5
12 x 10	293.9	328.9	254	610	305	483	363.6	—	339.7	—	81.0	285.8	609.6	117.5	—	371.5
12 x 12	360.2	407.8	305	610	305	483	398.5	—	374.7	—	81.0	320.7	609.6	117.5	—	371.5

KF Series FA/FAE Dimensional Data




Dimensional Data (in., mm), 2"FP-12"FP, Class 300, API 6D & ASME B16.34


Size (in.)	Weight (lbs.)		Dimension (in.)													
	Valve Only	w/Gear Op.	A	B	C	D	E	F Top of Handle	F CL of H/Whl.	G	H	U	Y	Z	AA	BB
2 x 2	35	48	2	8.50	4.25	6.50	4.94	6.88	5.00	8.50	1.06	3.88	8	2.75	3.56	7.19
3 x 2	42	55	2	11.13	5.56	8.25	4.94	6.88	5.00	8.50	1.06	3.88	8	2.75	3.56	7.19
3 x 3	63	76	3	11.13	6.00	8.25	6.63	8.25	6.50	15.00	1.25	5.38	8	2.75	4.50	7.19
4 x 3	83	96	3	12.00	6.00	10.00	6.63	8.25	6.50	15.00	1.25	5.38	8	2.75	4.50	7.19
4 x 4	114	127	4	12.00	6.00	10.00	7.44	9.00	7.31	15.00	1.25	6.19	8	2.75	5.25	7.19
6 x 4	160	173	4	15.88	7.94	12.50	7.44	9.00	7.31	15.00	1.25	6.19	8	2.75	5.25	7.19
6 x 6	282	312	6	15.88	7.94	12.50	9.50	10.81	9.25	48.00	2.09	7.00	14	2.50	—	9.38
8 x 6	352	382	6	19.75	9.88	15.00	9.50	10.81	9.25	48.00	2.09	7.00	14	2.50	—	9.38
8 x 8	481	545	8	19.75	9.88	15.00	11.56	12.59	10.38	48.31	2.38	8.75	18	3.50	—	11.94
10 x 8	597	661	8	22.38	11.19	17.50	11.56	12.59	10.38	48.31	2.38	8.75	18	3.50	—	11.94
10 x 10	735	840	10	22.38	11.19	17.50	14.31	—	13.38	—	3.19	11.25	24	4.63	—	14.63
12 x 10	904	1009	10	25.50	12.75	20.50	14.31	—	13.38	—	3.19	11.25	24	4.63	—	14.63
12 x 12	1083	1188	12	25.50	12.75	20.50	15.69	—	14.75	—	3.19	12.63	24	4.63	—	14.63

Size (in.)	Weight (kg)		Dimension (mm)													
	Valve Only	w/Gear Op.	A	B	C	D	E	F Top of Handle	F CL of H/Whl.	G	H	U	Y	Z	AA	BB
2 x 2	15.9	21.8	50.8	215.9	108.0	165.1	125.4	174.6	127	216.9	27.0	98.4	203.2	69.9	90.5	182.6
3 x 2	19.1	24.9	50.8	282.6	141.3	209.6	125.4	174.6	127	216.9	27.0	98.4	203.2	69.9	90.5	182.6
3 x 3	28.6	34.5	76.2	282.6	152.4	209.6	168.3	209.6	165	381	31.8	136.3	203.2	69.9	114.3	182.6
4 x 3	37.6	43.5	76.2	304.8	152.4	254	168.3	209.6	165	381	31.8	136.3	203.2	69.9	114.3	182.6
4 x 4	51.7	57.6	101.6	304.8	152.4	254	188.9	228.6	185.7	381	31.8	157.2	203.2	69.9	114.3	182.6
6 x 4	72.6	78.5	101.6	403.2	201.6	317.5	188.9	228.6	185.7	381	31.8	157.2	203.2	69.9	133.4	182.6
6 x 6	127.9	141.5	152	403.2	201.6	317.5	241	274.6	235.0	1219	53.2	177.8	355.6	63.5	133.4	238.1
8 x 6	159.7	173.3	152	501.7	250.8	381	241	274.6	235.0	1219	53.2	177.8	355.6	63.5	—	238.1
8 x 8	218.2	247.2	203	501.7	250.8	381	293.7	319.9	263.5	1227	60.3	222.3	457.2	88.9	—	303.2
10 x 8	270.8	299.8	203	568.3	281.0	444.5	293.7	319.9	263.5	1227	60.3	222.3	457.2	88.9	—	303.2
10 x 10	333.4	381.0	254	568.3	281.0	444.5	363.6	—	339.7	—	81.0	285.8	609.6	117.5	—	371.5
12 x 10	410.0	457.7	254	647.7	323.9	520.7	363.6	—	339.7	—	81.0	285.8	609.6	117.5	—	371.5
12 x 12	491.2	538.9	305	647.7	323.9	520.7	398.5	—	374.7	—	81.0	320.7	609.6	117.5	—	371.5


KF Series FA/FAE Topworks & Stem Data (in., mm)




2"FP-6"RP
Flatted Stem



6"FP-10"RP
Flatted Stem



10"FP-12"FP
Stem w/Square Key





Bore Size (in.)	Pressure Class	Dimension (in.)								
		H	JD Stem Dia.	K	P Hole Depth	Q	R	S Threaded Hole	CC	DD
2	150	1.06	.873/.867	.558/.554	thru	—	—	—	4.13	—
2	300	1.06	.873/.867	.558/.554	—	—	—	—	4.13	—
3	150	1.25	1.246/1.240	.748/.744	—	—	—	—	4.13	—
3	300	1.25	1.246/1.240	.748/.744	—	—	—	—	4.13	—
4	150	1.25	1.246/1.240	.748/.744	—	—	—	—	4.13	—
4	300	1.25	1.246/1.240	.748/.744	—	—	—	—	4.13	—
6	150	2.09	1.999/1.995	1.249/1.245	.75	3.38	2.00	3/8-16	5.13	3.13
6	300	2.09	1.999/1.995	1.249/1.245	.75	4.50	2.38	1/2-13	5.63	3.50
8	150	2.38	2.499/2.495	1.749/1.745	1.00	4.63	2.88	1/2-13	6.25	4.13
8	300	2.38	2.499/2.495	1.749/1.745	1.00	4.63	2.88	1/2-13	6.25	4.13
10	150	3.19	2.874/2.871	.75 Sq.	1.13	6.00	3.50	5/8-11	7.50	5.00
10	300	3.19	2.874/2.871	.75 Sq.	1.13	6.00	3.50	5/8-11	7.50	5.00
12	150	3.19	2.874/2.871	.75 Sq.	1.13	6.00	3.50	5/8-11	7.50	5.00
12	300	3.19	2.874/2.871	.75 Sq.	1.13	6.00	3.50	5/8-11	7.50	5.00


Bore Size (in.)	Pressure Class	Dimension (mm)								
		H	JD Stem Dia.	K	P Hole Depth	Q	R	S Threaded Hole	CC	DD
2	150	27.0	22.17/22.02	14.17/14.07	thru	—	—	—	104.8	—
2	300	27.0	22.17/22.02	14.17/14.07	—	—	—	—	104.8	—
3	150	31.8	31.65/31.50	19.00/18.90	—	—	—	—	104.8	—
3	300	31.8	31.65/31.50	19.00/18.90	—	—	—	—	104.8	—
4	150	31.8	31.65/31.50	19.00/18.90	—	—	—	—	104.8	—
4	300	31.8	31.65/31.50	19.00/18.90	—	—	—	—	104.8	—
6	150	53.2	50.77/50.67	31.72/31.62	19.1	85.7	50.8	3/8-16	130.2	79.4
6	300	53.2	50.77/50.67	31.72/31.62	19.1	114.3	60.3	1/2-13	142.9	88.9
8	150	60.3	63.47/63.37	44.42/44.32	25.4	117.5	73.0	1/2-13	158.8	104.8
8	300	60.3	63.47/63.37	44.42/44.32	25.4	117.5	73.0	1/2-13	158.8	104.8
10	150	81.0	73.00/72.92	19.1 Sq.	28.6	152.4	88.9	5/8-11	190.5	127
10	300	81.0	73.00/72.92	19.1 Sq.	28.6	152.4	88.9	5/8-11	190.5	127
12	150	81.0	73.00/72.92	19.1 Sq.	28.6	152.4	88.9	5/8-11	190.5	127
12	300	81.0	73.00/72.92	19.1 Sq.	28.6	152.4	88.9	5/8-11	190.5	127

KF Series FA/FAE Engineering Data

Pressure Temperature







Low Temperature Limits

Body Material	°F	°C
LCC	-50	-45.6
WCB	-20	-28.9
CF8M	-50	-45.6

Seat Material	°F	°C
Devlon® V	-50	-45.6
Teflon®	-50	-45.6
HT4 (PEEK™)	-50	-45.6

Seal Material	°F	°C
Aflas®	+32	0
Low Temp Buna N	-50	-45.6
Viton®	-15	-26.1
J. Walker® Viton®	+10	-12.2
HNBR	-40	-40
EPDM	-50	-45.6
LT HNBR	-50	-45.6

Note: Consult factory for service above 325°F.
*For chemical service. **For water and steam service only.

Flow Coefficient (C_V)

Size (in.)	Class 150	Class 300
2FP	420	420
3RP	225	225
3FP	1050	1050
4RP	600	600
4FP	2000	2000
6RP	910	910
6FP	5470	5100
8RP	2500	2400
8FP	10,750	10,300
10RP	5000	4825
10FP	17,775	16,300
12RP	8400	8200
12FP	26,750	26,000

Method of Calculating Flow

The flow coefficient "C_V" of a valve is the flow rate of water (gallons/minute) through a fully opened valve, with a pressure drop of 1 psi across the valve. To find the flow of liquid through valve from the Cv, use the following formulas:

Liquid Flow

QL = Flow rate of liquid (gal./min.)
ΔP = Differential pressure across the valve (psi)
G = Specific gravity of liquid (for water, G=1)

$$QL = C_V\sqrt{\frac{\Delta P}{G}}$$

Gas Flow

Qg = Flow rate of gas (CFH at STP)
P2 = Outlet pressure (psia)
g = Specific gravity of gas (for air, g=1.000)


$$Qg = 61C_V\sqrt{\frac{P2\,\Delta P}{g}}$$

For non-critical flow

$$\left\{\frac{\Delta P}{P2} < 1.0\right\}$$

CIRCOR ENERGY | KF Valves

KF Series FA/FAE Optional Accessories & Installation



Pups

Buttweld valves may be supplied with transition pieces (PUPS) to avoid any risk of seat and seal damage during welding and post weld heat treatment operations. Length of pups and type of pipe and grade to be specified by customer.

Extensions

KF series FA/FAE ball valves are available for below ground or buried service with fully operational extensions to meet your specifications. Body bleed and sealant injection functions are maintained along with total valve control by manual or powered actuators. Extension dimensions for gear operator or actuator are given with reference from the valve center line to the center of hand wheel.

Actuation

The bonnet design on KF series FA/FAE ball valves permits easy adaptation to mount manual, electric, hydraulic or pneumatic actuators.

External Coating


KF series FA/FAE ball valves can be coated for added corrosion protection to meet specific application requirements. Coating is available upon request. Ask your KF Valves representative for more information on this special coating process.

Metal Seated Ball Valves

KF series FA/FAE metal seated ball valves have been designed to provide a reliable, efficient and safe method to handle services where higher temperatures and/or the presence of solid particles in the fluid make it not recommended to use soft seated ball valves.

Subsea Options

Subsea valves are optionally available with coal tar epoxy coating (18 to 20 mils), xylan® coated bolting and subsea gear operators.



Installation

Flange Ends (RF)

- Series FA/FAE ball valves may be mounted in either vertical or horizontal piping systems. The stem may be positioned vertically or horizontally.
- Mating flanges must be correctly aligned. Alignment includes bolt hole placement, parallelism and perpendicularity.
- Flange studs or bolting must be correct size and properly tightened.
- Properly constructed piping systems do not cause undo stress in valve assemblies. Valves are not intended to make up for insufficient pipe tolerances.

Weld Ends (WE)

- Keep ball in open position prior to installation/welding of KF series FA/FAE weld end ball valves.
- Place the valve in position by aligning weld ends to the pipe. Prior to welding it is imperative that all welding surfaces be clean from contamination such as dirt, dust and grease which may affect weld performance.
- Caution: During the welding process, valve body temperatures should be monitored around the circumference at a location in line with the sealant injection fittings. The temperatures at this plane should be checked with temperature stick or other reliable temperature indicator and not allowed to exceed 300°F. This precaution is necessary to assure that non-metallic seals do not suffer heat damage.
- Tack weld valve in position and check for proper alignment.
- Finish weld following proper weld procedure for material grade and condition and the above caution.



CIRCOR Energy is a global manufacturer of highly engineered valve and pipeline products that continuously develops precision technologies to improve our customers' ability to control the flow of the world's natural resources, from sub-sea to land, and in severe environments.

Continuously Improving Flow Control. Worldwide.

United States
Oklahoma City
1500 S.E. 89th St.
Oklahoma City, OK 73149
Tel: 405.631.1533
Fax: 405.631.5034
sales@circorenergy.com

Houston
Corporate & Sales
945 Bunker Hill, Suite 650
Houston, TX 77024
Tel: 832.912.8333
sales@circorenergy.com

Canada
Calgary
Suite 2604, 308 4th Ave. SW
Calgary, Alberta T2P 0H7
Tel: 403.266.6500
Fax: 403.266.5088
sales.canada@circor.com

Edmonton
9430-39th Avenue
Edmonton, Alberta T6E 5T9
Tel: 780.463.8633
Fax: 780.461.1588
sales.canada@circor.com

China
10# Qun Xing San Road
Loufeng District Suzhou
Industry Park
China Post Code: 215006
Tel: +86 512 62516088
Fax: +86 512 62513119
sales.china@circor.com

Asia Pacific
10 Woodgrove View
Singapore 738113
Tel: +65 63101595
Fax: +65 62691973
sales.asia@circor.com

Brazil
1480, Eugenio Losso District St.
Unileste - 13422-180
Piracicaba - Sao Paulo - Brazil
Tel: +55.19.3124-3124
Fax : +55.19.3414-3722
sfvalvulas@circor.com.br

Latin America
1500 S.E. 89th St.
Oklahoma City, OK 73149
Tel: 405.631.1533
Fax: 405.631.5034
sales@circorenergy.com

U.A.E.
P.O. Box: 263202
Unit FZS5 AA01
Jebel Ali Free Zone
Dubai, UAE.
Tel:+971.4.8866128
Fax: +971.4.8866129
sales.dubai@circor.com

CIRCOR ENERGY

www.circorenergy.com

©2013 CIRCOR Energy. All rights reserved.
KF-FA/FAE-NOVEMBER-2013-2UP-HP

KF Valves reserves the right to change designs, materials, or specifications without notice or without obligation to furnish or install such changes on products previously or subsequently sold.

Inconel® is a registered trademark of Special Metals Corporation, USA • Xylan® is a registered trademark of Whitford • Devlon® is a registered trademark of Devol Engineering, Ltd.• Viton® is a registered trademark of DuPont Dow Elastomers. Aflas® is a registered trademark of Asahi Glass. • Elast-O-Lion® and James Walker® are registered trademarks of James Walker.• Teflon® is a registered trademark of DuPont. • PEEK™ is a trademark of Victrex Plc.